

**CATV (RG-6) / Part No.: CX-4RG6XXN-C2CP\* (60%)**
**Description**

- Rated temperature: 75°C
- Reference standard: GR-2881-CORE, SCTE IPS-SP-001, UL 1655, UL 13, UL444
- Solid Copper Clad Steel conductor
- Skin foam HDPE insulation
- Passes UL Riser flame test & CSA FT4 vertical flame test
- Packaging: Reel in Box, Reel

**Application**

- Drop cable for CATV and MATV distribution
- Networking that integrates voice, video and data signal transmission
- Direct burial drop cable

**Product Figure**

**Physical Characteristics**

<b>Structure</b>	<b>Construction</b>	18AWG CCS+M
	<b>Conductor Dimension (mm)</b>	1.02
<b>Insulation</b>	<b>Conductor Material</b>	Solid Copper Clad Steel
	<b>Insulation Material</b>	Skin Foam HDPE
<b>Shield</b>	<b>Insulation Dimension (mm)</b>	4.57
	<b>Outer Shield &amp; Material</b>	AL + 60% AL Braiding + MESSENGER
<b>Outer Jacket</b>	<b>Messenger</b>	Yes
	<b>Outer Jacket Material</b>	PVC
<b>Mechanical Characteristics</b>	<b>Overall Nominal Diameter (mm)</b>	6.95*10.65
	<b>Operating Temp. Range</b>	-20~75°C
	<b>Bulk Cable Weight (KG)</b>	64.75KG
	<b>Nom. Mutual Capacitance @ 1kHz</b>	≤53.1nF /100M
<b>Electrical Characteristics</b>	<b>Flame Test</b>	CMX, CM, CMG, CMR
	<b>Nominal Velocity of Propagation</b>	82%
	<b>Max. Conductor DC Resistance @ 20 Deg. C</b>	102Ω /100M

**CATV High Frequency Electrical Characteristics**

RG-59				
Frequency(MHZ)	ATT(dB/100m)	Impedance	SRL	Vel. of Prop(%)
5	4.00	75± 3	≥20	82
55	6.76	75± 3	≥20	82
211	12.93	75± 3	≥20	82
250	14.10	75± 3	≥20	82
270	14.67	75± 3	≥20	82
300	15.49	75± 3	≥20	82
350	16.79	75± 3	≥20	82
400	17.98	75± 3	≥20	82
450	19.13	75± 3	≥20	82
500	20.20	75± 3	≥20	82
600	22.27	75± 3	≥20	82
750	25.00	75± 3	≥20	82
870	27.03	75± 3	≥20	82
1000	29.10	75± 3	≥20	82

\* Custom configuration is available upon request.

